

**CRAWFORD COUNTY FAIR DEMOLITION DERBY 2010 RULES
80's & NEWER & COMPACT CAR**

GENERAL: All entrants must be 18 years or older. Any entrant under 18 must have notarized release signed by parent or guardian. The Crawford County Agricultural Society or any of its members will not be held responsible for injuries or damage to cars, entrant, mechanic, or car owners.

Any protest must be done 10 minutes prior to 1st heat. A protest fee of \$150.00 must be made.

All winning cars must be reinspected after feature to confirm car is legal. If you are caught cheating you will forfeit any entry fee, money won, or trophy. Derby official is final decision.

Any American made 1980 or newer hardtop may be used, except for limousines, hearses, ambulances, convertibles, or checker cab.

Drivers must wear a crash helmet with eye protection (full face helmet is recommended) long pants, long sleeve shirt, & seat belt are required. Driver will not extend any part of his/her body outside of the car at anytime while heat is running.

Drivers DOOR & PASS. Door must be painted white.

All cars must have brakes before inspection.

All preceding rules apply for FULLSIZE & COMPACT except where noted.

Compact Wheel Base 106" MAX.

ENGINE: Engine Mounts may be chained or welded. Engine swapping is allowed GM to Ford, Ford to Chrysler, ect. Compacts must have 4 cylinder. Headers to exist straight up through hood. Distributor protector may be used but only bolted to motor and trans. No kickers to inside cage, bar, frame, or body.

GAS TANK: All gas tanks must be moved to back seat. They must be securely fastened & covered before inspection. All tanks must be vented outside vehicle. No tank larger than 5 gal. Electric fuel pump may be used must have on/off switch on dash clearly marked. Gas tank protectors may be used must be NO WIDER THAN INSIDE OF FRAME & 2" OFF FROM REAR PANEL NO KICKERS IN ANY DIRECTION [this is not a frame roll reinforcements]


ELECTRICAL & BATTERY: One battery of any size may be used. It must be securely fastened and covered in drivers' compartment before inspection. Solenoid, modules, regulator, ect. May be moved but must remain under hood and in front of firewall.

DRIVERS COMPARTMENT: May have max 3" diameter pipe behind drivers' seat & across dash. No kickers to floor or firewall. Driver's door only may be reinforced. Passenger side may have bar inside drivers' compartment but MUST NOT TOUCH ANY PART OF BODY.

TRANSMISSION: Trans cooler may be used, must have some type of shield protecting driver in case of cooler rupture. All cooler line must be covered.

FRAME: MUST BE STOCK, No planting frame for any reason inside or outside. No rewelding frame seams anywhere for any reason. Body mounts must remain in place or replace with like material, body bolts may be changed no larger than 5/8 bolt with 3" washer. Notching or prebending frame is allowed. Strap or chain may be used from hump to hump but cannot go around axle.

Hump strap may be used. TOP OF STRAP MUST BE AT LEAST 3" FROM BOTTOM OF HUMPS, 3" WIDE, 24" LENGTH, 1/4" THICK MAX. STRAP SIZE, ONE [1] STRAP PER SIDE. THIS RULE DOES NOT APPLY TO COMPACT CARS.



Continued on next page

SUSPENSION: Must be stock, No welding shocks, no air shocks. No truck rear ends 5 lug only must be automotive type. Rear Coil springs may be wired or welded only to hold in place. Coil spring cannot be welded solid. Coil spring swap is permitted NO leaf spring conversions. Front A-Arm CANNOT be welded. Chaining or bolting is allowed.

BUMPERS: May be welded to plate & plate welded to frame NO EXTRA PLATE OR BRACING, IF FRONT FRAME CUT SHORT MUST BE 1" INSPECTION HOLE IN FRAME BEHIND BUMPER. Must be factory style bumper. NO PRE 1980 BUMPERS. BUMPER SHOCKS ARE OPTIONAL.

TIRES: Any AUTOMOTIVE type tire may be used must have DOT NUMBER & be street legal. No loading tires, No wheel weights, No studded tires. Valve stem protectors may be used.

BODY: No inner body seam welding for any reason. Doors & trunk may be welded but not solid, MAX 12"-4" plate or weld & skip 12". If trunk is welded must have hole for inspection, trunk is either on or off must be in stock position NO WELDING OR TRUCKING, BODY CANNOT BE WELDED TO BUMPER. 16" Min rear bumper height from bottom of bumper. Hoods may be chained or wired in 4 places must be opened for inspection. 2 front hood pins may go through core support & frame 5/8 rod MAX.

RADIATOR: Must be stock automotive type radiator & remain in original position NO ANTIFREEZE.

IF IT DOESN'T SAY DON'T DO IT!

DISQUALIFICATIONS: Any INTENTIONAL hitting drivers door
Any hot rodding in pits
Any car leaking gas in the arena
Any arguing with officials
Any sandbagging
1st offense caught cheating.

Due to space limitations in the pit area, three tickets will be issued. One ticket for driver, One ticket for mechanic, One ticket for tow vehicle. No other vehicle will be allowed in the pit area.

ANY QUESTIONS CALL TOM MOEHLE @ 419 668-0630 OR 419 744-4753